



GOODYEAR DURA TORQUE R-1

- Excellent roadability provided by the overlapping center lugs
- Traction in a wide range of sizes due to its long bar design
- Long wear and durability from its braced lug design
- Easy lug cleanability



Tire Size	Catalog #	TL/TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lbs)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Tread Depth (32nd in)	RCI	SRI
7-16	4DQ666	TL	6	36	1,100	6L, 6.00F, 6LB	7.6	29.5	13.8	89	32	--	350

Inflation Pressure (psi)	25 mph (lbs)	20 mph (lbs)	15 mph (lbs)	10 mph (lbs)	5 mph (lbs)
12	525	585	625	760	820
16	610	675	720	880	945
20	705	785	840	1,020	1,100
24	770	855	915	1,110	1,195
28	840	935	1,000	1,215	1,310
32	920	1,020	1,090	1,325	1,430
34	945	1,050	1,125	1,365	1,470
36	990	1,100	1,175	1,430	1,540

Tire Size	Catalog #	TL/TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lbs)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Tread Depth (32nd in)	RCI	SRI
8.3-24	4DQ684	TL	6	34	1,610	W7	8.4	39.4	18.5	119	35	34	475

Inflation Pressure (psi)	30 mph (lbs)	25 mph (lbs)	20 mph (lbs)	15 mph (lbs)	10 mph (lbs)	5 mph (lbs)	Cyclic Service		
							Inflation Pressure (psi)	10 mph (lbs)	6 mph (lbs)
12	800	880	940	975	1,180	1,320	16	1,495	1,645
16	930	1,020	1,090	1,130	1,365	1,530	20	1,735	1,905
20	1,065	1,170	1,250	1,300	1,570	1,755	26	1,990	2,190
24	1,200	1,320	1,410	1,465	1,770	1,980	32	2,245	2,470
28	1,300	1,430	1,530	1,585	1,915	2,145	36	2,430	2,675
30	1,345	1,480	1,585	1,645	1,985	2,220	40	2,515	2,770
32	1,430	1,570	1,680	1,745	2,105	2,355	42	2,670	2,935
34	1,465	1,610	1,725	1,785	2,155	2,415	44	2,735	3,010

Tire Size	Catalog #	TL/TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lbs)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Tread Depth (32nd in)	RCI	SRI
9.5-16	4DQ695	TL	6	30	1,390	W8L, 8LB	9.6	33.4	15.4	100	36	31	400

Inflation Pressure (psi)	30 mph (lbs)	25 mph (lbs)	20 mph (lbs)	15 mph (lbs)	10 mph (lbs)	5 mph (lbs)	Cyclic Service		
							Inflation Pressure (psi)	10 mph (lbs)	6 mph (lbs)
12	750	825	885	915	1,105	1,240	16	1,405	1,545
16	880	965	1,035	1,070	1,295	1,450	20	1,640	1,805
20	1,000	1,100	1,175	1,220	1,475	1,650	26	1,870	2,055
22	1,065	1,170	1,250	1,300	1,570	1,755	28	1,990	2,190
24	1,120	1,230	1,315	1,365	1,650	1,845	32	2,090	2,300
26	1,165	1,280	1,370	1,420	1,715	1,920	34	2,175	2,395
28	1,240	1,360	1,455	1,510	1,820	2,040	36	2,310	2,545
30	1,265	1,390	1,485	1,545	1,865	2,085	40	2,365	2,600

Tire Size	Catalog #	TL/TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lbs)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Tread Depth (32nd in)	RCI	SRI
9.5-16	4DQ695	TL	6	30	1,390	W8L, 8LB	9.6	33.4	15.4	100	36	31	400

Inflation Pressure (psi)	30 mph (lbs)	25 mph (lbs)	20 mph (lbs)	15 mph (lbs)	10 mph (lbs)	5 mph (lbs)
12	750	825	885	915	1,105	1,240
16	880	965	1,035	1,070	1,295	1,450
20	1,000	1,100	1,175	1,220	1,475	1,650
22	1,065	1,170	1,250	1,300	1,570	1,755
24	1,120	1,230	1,315	1,365	1,650	1,845
26	1,165	1,280	1,370	1,420	1,715	1,920
28	1,240	1,360	1,455	1,510	1,820	2,040
30	1,265	1,390	1,485	1,545	1,865	2,085

Cyclic Service		
Inflation Pressure (psi)	10 mph (lbs)	6 mph (lbs)
16	1,405	1,545
20	1,640	1,805
26	1,870	2,055
28	1,990	2,190
32	2,090	2,300
34	2,175	2,395
36	2,310	2,545
40	2,365	2,600