

HI-FLOTATION I-1

APLICACIONES



Ideal para aplicación en ejes libres de **Implementos agrícolas, Graneleros y Sembradoras.**

Tiene una banda con rayas anchas y surcos profundos, que ofrece una excelente tracción. Su talón está reforzado por un grueso reborde de caucho, lo que garantiza un montaje seguro y resistente.

6
AÑOS DE
GARANTÍA



BENEFICIOS

- Banda de rodaje con **mayor área de contacto** del neumático con el suelo y mayor fluctuación.
- La carcasa reforzada tiene **protección adicional** contra cortes y laceraciones.
- Diseño de rayas que proporciona una **mejor autolimpieza** y una **mayor estabilidad** y distribución uniforme.



CONSTRUCCIÓN
ROBUSTA



EXCELENTE
MANEJABILIDAD



MEJOR
AUTOLIMPIEZA

HI-FLOTATION

- Noted for its maximum flotation
- Features wide tread design, large footprint, deep grooves and low section height design



Products

Name	Catalog Number	Tire Size	Design	Industry Code	TT/TL	Load/Ply Rating	Rated Inflation Pressure (psi)	Rated Speed (mph)	Rated Load (lbs)	Recom'd Rim	Overall Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Weight (lbs)	Tread Depth (32nd in)
11L-15SL 113B/8PR Hi-Flotation	410318TE	11L-15SL	Hi-Flotation	I-1	TL	8	36	30.0	2540	8LB	10.76	30.84	13.75	90.28	42	11
12.5L-15SL 10 Hi-Flotation TL	410341	12.5L-15SL	Hi-Flotation	I-1	TL	10	44	30.0	3420	10LB	11.70	32.30	14.39	94.51	52	11
12.5L-16SL 14 Hi-Flotation TL	41L353	12.5L-16SL	Hi-Flotation	I-1	TL	14	56	30.0	4180	10LB	11.90	31.90	14.30	95.00	59	11
14L-16.1SL 12 Hi-Flotation TL	410362	14L-16.1SL	Hi-Flotation	I-1	TL	12	44	30.0	4680	W11C	14.40	36.80	16.47	107.97	86	12
14L-16.1SL 8 Hi-Flotation TL	410368	14L-16.1SL	Hi-Flotation	I-1	TL	8	32	30.0	3860	W11C	14.20	37.20	16.32	107.84	76	12
16.5L-16.1SL 138B/10PR Hi-Flot	410350TE	16.5L-16.1SL	Hi-Flotation	I-1	TL	10	36	30.0	5200	W14CH	17.10	40.90	18.00	118.79	105	14
16.5L-16.1SL 14 Hi-Flotation	4103L1	16.5L-16.1SL	Hi-Flotation	I-1	TL	14	48	30.0	6400	W14CH	17.10	40.60	18.07	118.72	115	14
19L-16.1SL 10 Hi-Flotation TL	4103H7	19L-16.1SL	Hi-Flotation	I-1	TL	10	32	30.0	6000	W16CH	19.40	43.98	19.16	126.96	128	17
19L-16.1SL 18 Hi-Flotation TL	4109H7	19L-16.1SL	Hi-Flotation	I-1	TL	18	52	30.0	8250	W16CH	19.30	44.53	19.92	130.61	139	16
21.5L-16.1SL 10PR/146B Hi-Flot	41L349TE	21.5L-16.1SL	Hi-Flotation	I-1	TL	10	28	30.0	6600	W18CH	21.80	46.30	20.44	134.73	183	17