



### Recommended Vehicle Type & Position



# AEOLUS

## NEO AGB23 All-position

Suitable for all axles, urban and regional application use. Longer mileage with deeper tread depth and excellent sidewall protection which minimizes damage against obstacles.



**Longer Mileage**

**Durability**

**Low Rolling Resistance**

**Fatigue Resistance**

**New Appearance**



Size	PLY Rating	Overall Diameter (mm)	Overall Width (mm)	Max Load Single(kg)	Max Load Dual(kg)	Max Pressure Single(kPa)	Max Pressure Dual(kPa)	LI/SS	Second LI/SS	Tread Depth (mm)	DOT	M+S
11R22.5	18	1061	280	3150	2900	850	850	148/145J	151/148E	20	✓	✓
215/75R17.5	16	769	220	1750	1600	830	830	127/124M	---	15	✓	✓
215/75R17.5	16	769	220	1750	1600	830	830	127/124M	---	15	✓	✓
225/70R19.5	16	810	230	1900	1800	830	830	130/128L	---	15	✓	✓
245/70R19.5	18	854	250	2800	2650	900	900	144/142J	---	16	✓	✓
255/70R22.5	16	932	252	2500	2300	830	830	140/137J	---	16.5	✓	✓
265/70R19.5	18	872	259	2725	2575	830	830	143/141J	---	16	✓	✓
275/70R22.5	18	971	286	3350	3150	900	900	150/148J	152/148E	20.5	✓	✓
295/80R22.5	18	1063	310	3550	3250	900	900	152/149J	154/150E	18.5	✓	✓