



## Regional Application

### Recommended Tyre Position



- Recommended to use
- Permitted
- Not recommended to use

# AEOLUS NEO Allroads S

It's power-packed performance on winding, hilly roads, coupled with its high adaptability to regional routes, guarantees excellent mileage as well as minimum fuel consumption. Mile after mile.



**Km** Long Tread Life

**£** Fuel Efficiency

**S** Safety

**D** Durability

Size	PLY Rating	Overall Diameter (mm)	Overall Width (mm)	Max Load Single(kg)	Max Load Dual(kg)	Max Pressure Single(kPa)	Max Pressure Dual(kPa)	LI/SS	Second LI/SS	Tread Depth (mm)	DOT	M+S
205/75R17.5	14			1600	1500	760	760	124/122M	---	12.5	✓	✓
215/75R17.5	16	764	216	1700	1600	700	700	126/124M	---	13	✓	✓
215/75R17.5	18	764	216	2180	2060	850	850	135/133J	---	13	✓	✓
225/70R19.5	14	810	227	1800	1700	760	760	128/126M	---	14	✓	✓
225/75R17.5	16	778	221	1800	1700	760	760	129/127M	---	13	✓	✓
225/80R17.5	14	807	234	1850	1750	760	760	129/127L	---	15	✓	✓
235/75R17.5	16	795	238	2000	1900	775	775	132/130M	---	13	✓	✓
235/75R17.5	18	795	238	2725	2575	830	830	143/141J	---	13	✓	✓
245/70R17.5	18	792	250	2240	2120	850	850	136/134M	---	15	✓	✓
265/70R19.5	16	868	260	2500	2360	830	830	140/138M	---	13	✓	✓
275/70R22.5	18	963	281	3150	2900	900	900	148/145M	---	16.5	✓	✓
285/70R19.5	16	892	281	3000	2800	850	850	146/144L 145/143M	145/143M	14	✓	✓
295/80R22.5	18	1049	298	3750	3250	900	900	154/149M	---	16.5	✓	✓
315/70R22.5	18	1018	314	4000	3350	900	900	156/150L 154/150M	154/150M	15.5	✓	✓
315/80R22.5	18	1085	316	4250	3350	900	900	158/150L 154/150M	154/150M	16	✓	✓