



CARGOPOWER

CGC108+ All-position

Products designed for all position axle of trucks under all kinds of working conditions



Long Tread Life

Cut resistance

Good breaking

Grip



Size	PLY Rating	Overall Diameter (mm)	Overall Width (mm)	Max Load Single(kg)	Max Load Dual(kg)	Max Pressure Single(kPa)	Max Pressure Dual(kPa)	LI/SS	Second LI/SS	Tread Depth (mm)	DOT	M+S
11R22.5	16	1058	281	3000	2725	830	830	146/143L	148/145K	17	√	√
11R22.5	18	1059	280	3250	3000	930	930	149/146L		17	√	√
11R24.5	16	1098	288	3250	3000	830	830	149/146L		17	√	
12.00R20	20	1080	303	4000	3650	900	900	156/153K		17.5	√	√
12R22.5	18											
13R22.5	20			4000	3650	930	930	156/153L		18	√	√
215/75R17.5	18			2180	2060	830	830	135/133J		14	√	√
235/75R17.5	18			2725	2575	875	875	143/141J		16.5	√	√
255/70R22.5	16			2500	2300	830	830	140/137M		17	√	√
275/70R22.5	18			3150	2900	900	900	148/145M		17.5	√	√
295/80R22.5	18		303	3550	3250	900	900	152/149L		17	√	√
315/80R22.5	20	1077	313	4625	3750	900	900	161/154K		16.5	√	